

WEATHER SEAL WB

Water Repellent

DESCRIPTION

Conspec Weather Seal WB is a water-base penetrating sealer designed to protect concrete and masonry surfaces. Conspec Weather Seal WB treated surfaces greatly reduce water and de-icing salt intrusion to help protect the substrate from the damaging effects of freeze thaw cycling and corrosion. V.O.C. compliant.

USE

- Concrete Structures
- Masonry structures
- Side Walks
- Driveways
- Brick, stucco and stone surfaces

FEATURES

- Colorless and non-yellowing
- Dries tack-free and skid-resistant
- Long lasting protection for new as well as old concrete surfaces
- Reduces the effects of freeze-thaw cycling and weathering on concrete structures
- V.O.C. compliant - Water-base
- Excellent water repellency while maintaining breathability

VOC

0 g/L. Compliant with all US VOC regulations for including Federal EPA, OTC, LADCO, SCAQMD & CARB.

ESTIMATING GUIDE

Exact coverage will depend upon the porosity of surface and density

	Sq. FT./Gallon	Sq. M/Liter
Concrete (broom finish)	100-125	2.5-3.0
Concrete (smooth)	125-175	3.0-4.3
Concrete (steel trowel finish)	150-200	3.7-5.0
Stucco	100-150	2.5-3.7
Exposed Aggregate	100-150	2.5-3.7
Brick	100-175	2.5-4.3

PACKAGING

55 gal.(208L) drums & 5 gal.(18.9L) pails

STORAGE

KEEP FROM FREEZING. Shelf life is 12 months from date of manufacture in original unopened containers.

APPLICATION

New Concrete

Surface should be well cured (28 day minimum) using water, wet burlap, polyethylene curing paper, or dissipating resin based curing compound. Surface should be free of all curing residue, dust, debris, oil and other contaminants. Substrates must be absorptive to allow penetration of the Weather Seal WB. All joint sealant and caulks and patching should be in place before applying Conspec Weather Seal WB.

Old Concrete and Masonry

Remove any previously applied sealers, dirt, dust, tar, oil, etc. with pressure wash and Orange Peel or other appropriate measures to properly prepare the substrate. A membrane of any kind should be removed. Substrates must be absorptive to allow penetration of the Weather Seal WB.

Application Equipment

Roller, brush or low pressure sprayer.

Horizontal Surfaces

Flood surface using low pressure sprayer (airless sprayer 10 psi to 20 psi), roller, brush or broom. Broom or squeegee Conspec Weather Seal WB around for even distribution. Let the surface absorb the Conspec Weather Seal WB solution and follow-up immediately with a second application before the surface dries "wet on wet" method. Redistribute any puddles or free standing material.

Vertical Surfaces

Apply by sprayer, roller or brush in two applications from bottom up. Be sure to apply "wet on wet" method as described for horizontal surface. For vertical surfaces let the material run down 5 to 20 inches saturating the surface from contact point of spray. Follow up with second application before surface dries.

CLEAN-UP

Use water to clean tools and equipment.

WEATHER SEAL WB

Water Repellent

LIMITATIONS

FOR PROFESSIONAL USE ONLY

Apply only between 32°F -100°F (0°C-38°C).

Do not apply to a damp or wet surface.

Cover and protect all glass, aluminum, grass, shrubs, plants, or any other surface not intended to receive product from overspray.

Do not spray onto plastic or specialty coated glass, protect all asphalt based materials and painted surfaces.

Keep containers tightly sealed when not in use.

Not for use on porous concrete block.

Do not allow excess material to dry on the surface

PRECAUTIONS

READ MSDS PRIOR TO USING PRODUCT

- Keep material and containers away from high heat, open flames, sparks or other sources of ignition
- Use with adequate ventilation
- Wear protective clothing, gloves and eye protection (Goggles, Safety Glasses and/or Face Shield)
- Keep out of the reach of children
- Do not take internally
- In case of ingestion, seek medical help immediately
- May cause skin irritation upon contact, especially prolonged or repeated. If skin contact occurs, wash immediately with soap and water and seek medical help as needed
- If eye contact occurs, flush immediately with clean water and seek medical help as needed
- Dispose of waste material in accordance with federal, state and local requirements

DISTRIBUTED BY

NuWay Inc.

4190 Hoffmeister Avenue

St. Louis, Missouri 63125

314-544-1214

Website: www.nuwayinc.com

WARRANTY

Dayton Superior Corporation ("Dayton") warrants for 12 months from the date of manufacture or for the duration of the published product shelf life, whichever is less, that at the time of shipment by Dayton, the product is free of manufacturing defects and conforms to Dayton's product properties in force on the date of acceptance by Dayton of the order. Dayton shall only be liable under this warranty if the product has been applied, used, and stored in accordance with Dayton's instructions, especially surface preparation and installation, in force on the date of acceptance by Dayton of the order. The purchaser must examine the product when received and promptly notify Dayton in writing of any non-conformity before the product is used and no later than 30 days after such non-conformity is first discovered. If Dayton, in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the non-conforming product, refund the purchase price or issue a credit in the amount of the purchase price. This is the sole and exclusive remedy for breach of this warranty. Only a Dayton officer is authorized to modify this warranty. The information in this data sheet supersedes all other sales information received by the customer during the sales process. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.

Dayton shall not be liable in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustration of economic or business expectations; claims by third parties (other than for bodily injury), or economic losses of any kind; or for any special, incidental, indirect, consequential, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, its obligations under any contract for sale of product, even if Dayton could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this contract, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.